


Propbot

PL-50 2022

Amr, Apoorv, Cole, Johanan, Sajjad



Overview


- Client Introduction
- Problems with data collection
- Goal
- Requirements/Constraints
- Stakeholders
- Solution
- Our contribution
- Engineering Design

Client

- Conducts research on next-generation wireless communications and radar systems
- Requires high-quality wireless propagation data at various locations on UBC campus
- Researchers have a background in electrical and computer design




**Radio
Science
Lab**




Problem with Data Collection

- No standardized commercially available solution
- RSL Researchers need to manually transport heavy and expensive equipment
- Tedious and time consuming
- Affects many researchers around the world



Goal

- Automate the process of collecting wireless propagation data
- Autonomously navigate to points of interest set by a user
- Traverse UBC campus safely without posing any risk to itself or the public



Stakeholders

UBC RSL	User	Collect propagation data and GPS position
UBC Road Users	Community	Maintain safe distance and avoid collisions
Robot Operator	User	Teleoperation control and autonomy input
Transport Canada	Legal Personnel	Abide by legal guidelines
Future Capstone Teams	Developer	Clear and understandable documentation for future teams

Propbot's Initial State

Chassis Design and Construction

- Design and assembly of basic Propbot chassis
- Design choice of motors and drivers

Capstone PL-116

- Autonomy system design and implementation
- Component specifications and recommendation

2017

2018

2019

2020

2021

2022

Basic Integration

- Wiring and powering drivers
- Implementing basic loop operation

Capstone PL-50

- Vehicle interface design and implementation
- Integrating hardware and software



Constraints

- Mechanical Structure: chassis, suspension, rack module, hub motors
- Design recommendations: Ultrasonic sonar sensors, Depth camera, GPS module and LiDAR
- Autonomy Software: use of ROS framework for software (impacts how devices need to be interfaced), Move base for path planning.

Requirements



Motion: Execute longitudinal and rotational movements



Navigation: Facilitate motion commands from both a remote operator through RC and locally generated commands from the autonomous computer



Autonomy: Take a set of way points and autonomously generate a path of motion through the points that avoids obstacles



Safety: Must be safe and avoid/prevent collisions with objects and pedestrians


Design Principles

- **Safety:** Ensures safe operation for users and bystanders
- **Inheritable:** Future teams will not have to go through the same struggles we faced
- **Extendibility:** Features can be added without changing existing implementation
- **Testability:** Components and Features can be verified and validated according to known expectations

Our Contribution




Safe and reliable
teleoperation




Autonomy system
integration with sensor
suite




Robust power distribution
system






<https://www.youtube.com/watch?v=06ADRLlokVQ>

High-level System Overview




High-level Overview



Autonomy System Overview


Vehicle Interface System Overview

Legend	Definition
 	Remote Control
 	Autonomy System
 	Command Decision
 	Fail Safe Object Detection
 	Motor Control
LR	Long-range
SR	Short-range
FL	Front left
FR	Front right
BL	Back left
BR	Back right
LHS	Left hand side
RHS	Right hand side







Power Management

- Requirement is to provide the correct power to all components for at least 1.5hrs



Vehicle Interface System



Vehicle Interface Board



Functionality

- **Motor Control:** Propbot should be able to control the wheels
- **Teleoperation:** Propbot should be operable via RC transmitter
- **Obstacle Avoidance:** Propbot should have the capability to avoid obstacles

Motor Drivers

Roboteq SBL1360A (Proposed)

- Supports closed loop feedback, E-braking, CANBus
- Highly configurable via software and custom scripting



Generic motor controller (Legacy)

- Implemented as a risk mitigation step
- Supports basic speed, direction, and braking functionality
- Used for E-bikes with physical throttle but repurposed for Arduino PWM output using RC Filter





Sonar Sensors - Maxbotix MB1202/MB7040



MaxSonar MB1202
Wide beam, short distance



MaxSonar MB7040
Narrow beam, long distance



Sonar (Safety) Demo




<https://www.youtube.com/watch?v=Bj1LURdYbMI>

Teleoperation Control



FlySky i6X Radio Transmitter



Teleoperation Demo




<https://www.youtube.com/watch?v=AIADD6odR2I>

Autonomy System

Requirements

- **Sensor Integration:**
Interfaces with the sensors required to achieve localization and dynamic obstacle detection
- **Control:** Propbot should execute commands as issued by the Autonomy System



Autonomy System - Sensor Integration




Nvidia Jetson NX

Sensor	Purpose	Communication Protocol	Not Integrated
LiDAR: Velodyne Puck	Localization and Mapping, Navigation	Ethernet	Not Integrated
GPS: Neo-M8P	Global Positioning, Navigation	Serial	Integrated
IMU: BNo055	Localization	i2c	
Depth Camera: Intel RealSense D435	Object Detection, Visual odometry (speed estimation)	Serial	

Autonomy System - Sensor Integration

IMU




<https://www.youtube.com/watch?v=TuYOaY9iNyU>

Camera



<https://www.youtube.com/watch?v=m4SNWCZo97o>





200 m

GPS



<https://www.youtube.com/watch?v=uRIkpnUqnPM>

Autonomy System - Control





Differential Drive [1]

Autonomy System - Control




Autonomy System - Control



Skid Steer Drive [2]

Autonomy System - Comparing Drive Systems



Differential Drive




Skid Steer Drive

https://www.youtube.com/watch?v=gSyPa_sVO0w

<https://www.youtube.com/watch?v=KRZztzgfEgc>

Autonomy System - Integration



https://www.youtube.com/watch?v=fy8VR3S_pwQ



<https://www.youtube.com/watch?v=qEOlnOn-JPA>

Future Work

- Complete integration of LiDAR sensor
- Add wheel encoder or hall sensor for speed feedback
- Fine tuning Autonomy System configurations based on sensor input
- 3D mounts for the existing sonar sensors
- Weatherproofing



Thank you




References

- [1] hannahvsawiuk, “hannavsawiuk/Propbot” *GitHub*. [Online]. Available: https://github.com/hannahvsawiuk/Propbot/wiki/Software_Design. [Accessed: 29-Nov-2021].
- [2] “Knowledge: Wheel control theory,” Robot Platform. [Online]. Available: http://www.robotplatform.com/knowledge/Classification_of_Robots/wheel_control_theory.html. [Accessed: 18-Apr-2022].


Appendix

Full System Overview




System Overview - Vehicle Interface


Legend	Definition
	Remote Control
	Autonomy System
	Command Decision
	Fail Safe Object Detection
	Motor Control
LR	Long-range
SR	Short-range
FL	Front left
FR	Front right
BL	Back left
BR	Back right
LHS	Left hand side
RHS	Right hand side



System Overview - Vehicle Autonomy



Communication Protocols



Autonomy Computer - Jetson NX





```
top - 22:27:44 up 4:12, 5 users, load average: 1.43, 0.93, 0.76
Tasks: 314 total, 1 running, 313 sleeping, 0 stopped, 0 zombie
%cpu(s): 7.2 us, 5.9 sy, 0.0 ni, 84.6 id, 0.0 wa, 2.1 hi, 4.1 si, 0.0 st
KiB Mem : 7959996 total, 5668848 free, 1124840 used, 1269308 buff/cache
KiB Swap: 3979992 total, 3979992 free, 0 used, 6612164 avail Mem

  PID USER      PR  NI   VIRT    RES    SHR  S  %CPU  %MEM     TIME+ COMMAND
 21968 propbot  20   0 826956 62448 18240  S  11.2   0.8   0:13.04 move_base
21890 propbot  20   0 904356 42568 18760  S  10.2   0.5   0:12.28 cartographer_no
21871 propbot  20   0 423208 19848 10064  S   5.6   0.2   0:07.38 ekf_localizatio
20546 propbot  20   0 667840 63876 10304  S   3.6   0.8   0:11.74 rosmaster
21826 propbot  20   0 365904 24936 13012  S   3.3   0.3   0:04.14 robot_state_pub
21866 propbot  20   0 423208 21964 10136  S   3.3   0.3   0:04.08 ekf_localizatio
21918 propbot  20   0 422896 19200  9488  S   3.0   0.2   0:03.58 publish_slam_po
21950 propbot  20   0 1000620 152012 187904  S  2.6  1.9   0:05.01 rpld_odometry
21882 propbot  20   0 422284 19316  9576  S   2.6   0.2   0:03.62 navsat_transfor
21926 propbot  20   0 422896 19212  9496  S   2.6   0.2   0:03.65 publish_slam_po
21835 propbot  20   0 420660 17936  8844  S   2.3   0.2   0:02.59 twist_mux
21824 propbot  20   0 422468 19124  9916  S   2.0   0.2   0:02.57 marker_server
21910 propbot  20   0 376828 33784 14404  S   2.0   0.4   0:02.12 cartographer_oc
21939 propbot  20   0 772608 33016 12008  S   2.0   0.4   0:02.65 pointcloud_to_l
21842 propbot  20   0 346912 17828  8740  S   1.7   0.2   0:01.84 skid_steer_adju
21951 propbot  20   0 772100 30444 12724  S   1.7   0.4   0:02.14 pointcloud_to_l
21823 propbot  20   0 445920 59408  9908  S   1.3   0.7   0:02.04 python2
 5203 root      -SI   0   0   0   0   0   1.0  0.0   0:38.68 sugov:0
 7454 propbot  20   0 10992   4044   3172  R   0.7   0.1   1:28.97 top

RAM 1191/7773MB (lfb 1328x4MB) SWAP 0/3887MB (cached 0MB) CPU [21%@1190,11%@1190,18%@1190,17%@1190,16%@1190,14%@1190] EMC_FREQ 0% GR3D_FREQ 0% A0@47.5C GPU@46.5C lwlwlf@43C PMIC@50C AUX@47.5C CPU@48.5C thermal@47.5C
RAM 1192/7773MB (lfb 1328x4MB) SWAP 0/3887MB (cached 0MB) CPU [16%@1190,13%@1190,13%@1190,14%@1190,18%@1190,17%@1190] EMC_FREQ 0% GR3D_FREQ 0% A0@48C GPU@46.5C lwlwlf@43C PMIC@50C AUX@47.5C CPU@48.5C thermal@47.5C
RAM 1191/7773MB (lfb 1328x4MB) SWAP 0/3887MB (cached 0MB) CPU [18%@1190,13%@1190,14%@1190,11%@1190,17%@1190,14%@1190] EMC_FREQ 0% GR3D_FREQ 0% A0@48C GPU@47C lwlwlf@43C PMIC@50C AUX@47.5C CPU@48.5C thermal@47.5C
RAM 1191/7773MB (lfb 1328x4MB) SWAP 0/3887MB (cached 0MB) CPU [16%@1190,13%@1190,15%@1190,13%@1190,17%@1190,14%@1190] EMC_FREQ 0% GR3D_FREQ 0% A0@47.5C GPU@46.5C lwlwlf@43C PMIC@50C AUX@47.5C CPU@48.5C thermal@47.5C
RAM 1191/7773MB (lfb 1328x4MB) SWAP 0/3887MB (cached 0MB) CPU [21%@1190,16%@1190,16%@1190,14%@1190,14%@1190,14%@1190] EMC_FREQ 0% GR3D_FREQ 0% A0@48C GPU@46.5C lwlwlf@43C PMIC@50C AUX@47.5C CPU@48.5C thermal@47.5C
RAM 1191/7773MB (lfb 1328x4MB) SWAP 0/3887MB (cached 0MB) CPU [20%@1190,15%@1190,12%@1190,14%@1190,12%@1190,14%@1190] EMC_FREQ 0% GR3D_FREQ 0% A0@47.5C GPU@46.5C lwlwlf@43C PMIC@50C AUX@47.5C CPU@48.5C thermal@47.5C
RAM 1191/7773MB (lfb 1328x4MB) SWAP 0/3887MB (cached 0MB) CPU [18%@1190,12%@1190,12%@1190,11%@1190,14%@1190,14%@1190] EMC_FREQ 0% GR3D_FREQ 0% A0@48C GPU@46.5C lwlwlf@43C PMIC@50C AUX@47.5C CPU@48.5C thermal@47.5C
RAM 1192/7773MB (lfb 1328x4MB) SWAP 0/3887MB (cached 0MB) CPU [19%@1190,17%@1190,14%@1190,11%@1190,14%@1190,15%@1190] EMC_FREQ 0% GR3D_FREQ 0% A0@48C GPU@46.5C lwlwlf@43C PMIC@50C AUX@47.5C CPU@48.5C thermal@47.5C
RAM 1192/7773MB (lfb 1328x4MB) SWAP 0/3887MB (cached 0MB) CPU [20%@1190,14%@1190,14%@1190,18%@1190,16%@1190,15%@1190] EMC_FREQ 0% GR3D_FREQ 0% A0@47.5C GPU@46.5C lwlwlf@43C PMIC@50C AUX@48C CPU@48.5C thermal@47.5C
RAM 1192/7773MB (lfb 1328x4MB) SWAP 0/3887MB (cached 0MB) CPU [19%@1190,13%@1190,12%@1190,20%@1190,13%@1190,15%@1190] EMC_FREQ 0% GR3D_FREQ 0% A0@48C GPU@47C lwlwlf@43C PMIC@50C AUX@47.5C CPU@49C thermal@47.5C
RAM 1192/7773MB (lfb 1328x4MB) SWAP 0/3887MB (cached 0MB) CPU [18%@1574,18%@1574,14%@1574,15%@1574,14%@1574,16%@1574] EMC_FREQ 0% GR3D_FREQ 0% A0@47.5C GPU@46.5C lwlwlf@43C PMIC@50C AUX@47.5C CPU@48.5C thermal@47.5C
[1] 1:ssh*
```


LiDAR - Velodyne Puck VLP-16




- Provides 360 degree/100m range of high quality data (600000 points/sec) necessary for performing localization and mapping of Propbot's environment
- VLP-16 is the most popular LiDAR used in mobile robotics applications and contains excellent software support
- Communicates and is powered via Ethernet

LiDAR Mapping [1]

GPS - RTK System



GPS - Validation





Depth Camera - Intel RealSense D435


- 2 streams
 - Depth
 - 640 x 480, 30 fps
 - Color
 - 640 x 480, 30 fps
- Validated by running visual odometry node



Sensor Mapping



Legacy Motor Controllers



- Generic brushless DC motor controllers designed for use in DIY E-bike kits
- Variable analog voltage speed control
- Single-pin (Vcc/Gnd) direction and brake control

Roboteq Motor Controller Validation



<https://www.youtube.com/watch?v=buo4vMj-KM8&t=1s>



Roboteq Implementation Safety Features



Flyback Diode



Inline Fuse




Precharge Resistor





E-Stop

Motor Jitter: Root Cause Analysis




Legacy Motor Controller - RC Filter




Unfiltered Arduino PWM Output

Power Conversion and Delivery



Power Conversion





Autonomy System - Legacy


- Validation through simulation and visualization
- General Environment - not scenario specific
- Propbot control unrealistic




Simulation (ROS Gazebo)



Autonomy Validation - Adding Scenarios




Situation specific simulations




Resource-saving simulations


Autonomy Validation - Basic Setup




Validation Methods - Mocked Autonomy




Validation Methods - Integrated Simulation



MCC (Mapviz) - Legacy Design



Mission Command Centre



Data Logging

The screenshot displays the Mapviz application interface. On the left, the console shows a list of 141 messages, including errors like "map" and "odom" passed to lookupTransform argument target_frame does not exist, and informational messages about Datum UTM coordinates and latitude/longitude/altitude. Below the console are sections for "Exclude Messages..." and "Highlight Messages...".

The main area is divided into two panels. The top panel, titled "mapviz config (/home/pbuser/) - mapviz", contains configuration options for "Fixed Frame" (set to "map"), "Target Frame" (set to "<none>"), and "Use Latest Transforms" (checked). It also includes a "Background" section with a "tile_map (new display)" panel showing "Source" as "Stamen (terrain)" and a "Base URL" of "stamen.com/terrain/[level]/[x]/[y].png". Below this is a "plan_mission (new display)" panel with a "Start From Vehicle" checkbox and a "Preview Color" dropdown, along with buttons for "Upload Mission", "Clear", "Start Mission", "Pause Mission", "Resume Mission", and "End Mission".

The bottom panel, titled "navsat (new display)", shows "Color" (red), "Draw Style" (points), "Position Tolerance" (0.00), "Buffer Size" (0), and "Status" (OK). It includes "Add" and "Remove" buttons.


On the right side of the interface is a 3D terrain map showing a city street grid and surrounding greenery. A red dot and a cyan circle are visible on the map. The bottom right corner of the window shows the system tray with various icons and the text "Right Ctrl".

Data Collection




<https://www.youtube.com/watch?v=jgco001iaqM>

Speed Test Validation Results



Forward Max: 4.88km/hr
Forward Min: 1.78km/hr



Backward Max: 4.59km/hr
Backward Min: 1.01km/hr